## GULNAY X-RAY GENERATORS • CONTROLLERS • TUBES

# FC SERIES

# FC160HP







The Gulmay FC Series of high-voltage generators is available in either a standard 640W or higher power 1000W option. FC series generators are the ideal power supply when using traditional and high power series x-ray tubes for a variety of imaging techniques including analogue real-time imaging, digital flat panel imaging and linear imaging detectors. Used extensively in tyre inspection applications, the FC series is also ideal for use in food inspection, casting and welded assemblies, small parcel security, and a wide range of real-time NDT inspection applications.

The FC series incorporates an accurate feedback system that constantly monitors the x-ray tube mA and kV to ensure precise and stable output. The generator status is monitored by the internal electronics to maintain safe and reliable operation. The oil-filled high –voltage system provides greater thermal dissipation than resinfilled designs, increasing reliability and ensuring both a 100% duty cycle and full field serviceability

### WWW.GULMAY.COM

## X-RAY GENERATORS • CONTROLLERS • TUBES

Gulmay is a world leader in the design and manufacture of high voltage generators, x-ray generators and x-ray controllers.

Our extensive range of class-leading x-ray generators is complimented by a broad range of components including x-ray tubes from the world's leading manufacturers, high voltage cables, coolers, and complete turnkey sub-systems, configured and optimised for straightforward system integration.

#### PRODUCT SPECIFICATIONS

Max Power	1000W	Storage Temperature	-40°C to +70°C
kV Range	5-160kV	Operational Temperature	0°C to +40°C
kV Accuracy	±1% of Demand Value	Relative Humidity	95%
kV Reproducibility	Better Than ±0.05kV	Duty Cycle	100%
High Voltage Ripple	<10.0V/mA with 10M High Voltage Cable	INTERFACES	
mA Range	0-16mA	( omme	Analogue / RS232 /RS422
mA Accuracy	±0.5% of Demand Value		
mA Reproducibility	Better Than 2µA		
Input Voltage	230 V ± 10% 47-63 Hz	DIMENSIONS**	
Input Current	12.8A at 230V	Dimensions, mm	(W)360 x (H)482 x (D)613
Output Connector	R24	Weight (approx.)	102kgs

\*\* The Information provided is for reference purposes only. Actual specifications may differ depending on variant.

GULMAY Limited United Kingdom Telephone: +44 (0)1932 339850 Email : sales@gumay.com

GULMAY Incorporated United States Of America Telephone: + 1 678 482 6800 Email: sales@gulmayinc.com GULMAY GmbH Germany Telephone: +49 2151 9352720 Email: sales@gulmay.eu

GULMAY Electronic Equipment (Shanghai) Co.Ltd P.R.China Telephone: +86 21 6480 6580 Email: victor.qin@gulmay.cn



# **\***\*\*\*

### WWW.GULMAY.COM